



PC MASTER STATION PCC-650MX/PCC-650MXTS

PRODUCT CODE 51669/51720

FEATURES

- Complete intercom call handling functions
 - Call queue display
 - Call notification display
 - Call originate
 - Call answer/end/hold/forward
 - Group calling
 - Call monitoring
 - Central control location for duress/concierge calls
- Complete public address functionality
 - Make live and pre-recorded announcements
 - Broadcast tones, bells & alarms
 - Visual display of PA zones (unlimited number of zones depending on controller)
 - Selection and playback of recorded announcements
- Diagnostics and reporting
 - Alarm notifications including device state
- Send text message notifications to Jacques Video Monitor Stations
- Touchscreen compatible interface
- Map, grid and database views
- Upload multiple site maps to suit application/site
- Customisable layout/functions to suit application requirements

CUSTOMISATION

- Customisable GUI

PACKAGE CONTENTS

- TCH controller
- Screen, keyboard & mouse
- SMI Console Package
- DVI cable, power adapters and PoE converter

SPECIFICATIONS

Screen	PCC-650MX	PCC-650MXTS
	Size: 24" Resolution: 1920 x 1080 LED LCD Contrast ratio: 5000:1 Brightness: 250 cd/m² Viewing angle: 178° H, 178° V	Size: 22" Resolution: 1920 x 1080 LED LCD with PCAP touch screen Contrast ratio: 1000:1 Brightness: 250 cd/m² Viewing angle: 170° H, 160° V
Speaker	1 x 4 Ω, 3 W RMS (power rating)	
Speaker Amplifier	200 Hz - 7.0 kHz (output circuit frequency response -3 dB)	
Max. Acoustic Output	88 dB SPL @ 1 m, 0 dBFS 2.5 kHz (non-clipped) sine wave signal	
Microphone (SMI Console)	Microphone type: Gooseneck Output type: Uni-directional electret condenser Frequency response: 50 Hz – 18 kHz Sensitivity: -70 dB ± 3 dB @ 1 kHz	
Audio Streaming Bandwidth	256 kb/s both ways	
CPU	Intel Atom N270 1.6 GHz, 32-bit, single core with hyper threading	
Control Buttons	Stainless steel mechanical push-to-talk and volume buttons (SMI Console)	
Auxiliary Functions	Relay contacts (1 x NO/NC) max. 2 A @ 24 V d.c.	
Power Input	(100 – 240) V a.c. power cords/adapters included, 2 power outlets required	



Power Consumption	18 W max. (PCC-650MX) 25 W max. (PCC-650MXTS) 5 W max. (SMI-3B1)
Operating Temperature	(0 - 40) °C
Operating Humidity	(20 - 80) % relative humidity (non-condensing) (PCC-650MX/PCC-650MXTS) (10 - 90) % relative humidity (non-condensing) (SMI-3B1)
Cabling	UTP CAT-5/5e/6, multi-strand (0.75 mm²), max. 100 m
Dimensions	568 mm x 418 mm x 191 mm (PCC-650MX) 551 mm x 392 mm x 193 mm (PCC-650MXTS) 103 mm x 30.5 mm x 168 mm (SMI-3B1) 130 mm x 145 mm x 68 mm (SMI Console)
Weight	5 kg (PCC-650MX) 7.5 kg (PCC-650MX) 0.35 kg (SMI-3B1) 1.5 kg (SMI Console)
Environment	Indoor use only
Mounting Options	VESA desk stand (PCC-650MX/PCC-650MXTS) Mounting bracket, DIN rail clips (SMI-3B1) Desk mount (SMI Console)